EXCERIA G2 NVMe™SSD

Boost up your PC performance



Capacity

500GB, 1TB, 2TB

Max Sequential Read/Write Speed¹ 2.100/1.700 MB/s

Max Random Read/Write Speed²

500GB, 1TB: 400,000/400,000 IOPS 2TB: 360,000/400,000 IOPS

Features

BiCS FLASH™ NVMe™ 1.3c Technology M.2 2280 Form Factor PCle® Gen3 x4 SSD Utility Management Software

The new 2nd generation KIOXIA EXCERIA G2 SSD Series takes performance to the next level with up to 2,100 MB/s of sequential read speed¹, enabling faster boot ups, file transfers and system responsiveness. Leveraging BiCS FLASH™ 3D flash memory, this updated mainstream-class SSD series now offers up to 2TB of capacity in a M.2 2280 form factor suitable for both desktops and notebooks.

Performance Made Affordable

The KIOXIA EXCERIA SSD series redefines mainstream storage for everyday users that feel held back by SATA-based hardware. Say goodbye to hard drive lag and get a computing experience worthy of your applications. Compared to SATA SSDs, the EXCERIA G2 SSD series delivers balanced performance and value that will transform your system.





Small and Compact for an Easy Upgrade

Featuring a thin, single-sided M.2 2280 form factor, the EXCERIA G2 SSD series plugs directly into the motherboard, reducing additional cable clutter for a sleeker and an easy system upgrade.

NVMe[™] Technology

Why keep using an interface that was designed for hard drives? Utilizing the NVMe™ 1.3c technology, EXCERIA G2 SSD series reduce latency in your system's I/O path between your SSD and your CPU, resulting in smooth and responsive performance.





Cutting-Edge 3D Flash Memory

Each EXCERIA SSD is built with BiCS FLASH™ and a vertically stacked cell structure, delivering a cutting edge storage experience.

SSD Utility Management Software

The SSD Utility management software was designed to help your KIOXIA drive thrive and lets you be in control of maintenance, monitoring and more!

We highly recommend you install and update to the latest version to maximize your drive's performance and check its Percentage Life Left using the health gauge.



Specifications

Physical

Capacity

500GB, 1TB, 2TB

Interface

PCI Express® Base Specification Revision 3.1a (PCIe®)

Interface Maximum Speed

32 GT/s (PCle® Gen3 x4)

Interface Command

NVM Express™ Revision 1.3c command set

Form Factor

M.2 Type 2280-S2-M

Flash Memory Type

BiCS FLASH™ TLC

Dimension (Max: LxWxH)

80.15 mm x 22.15 mm x 2.23 mm

Drive Weight

500GB, 1TB: 6.8g (typ.) 2TB: 7.1g (typ.)

Performance

Max Sequential Read Speed¹

2,100 MB/s

Max Sequential Write Speed¹

1,700 MB/s

Max Random Read Speed²

500GB, 1TB: 400,000 IOPS 2TB: 360,000 IOPS Max Random Write Speed²

400,000 IOPS

Endurance: TBW³

500GB: 200TB 1TB: 400 TB 2TB: 800 TB **MTTF**

1.5 million hours

Environmental

Operating Temperature

0°C (Ta) to 85°C (Tc)

Storage Temperature

-40 °C to 85 °C

Certification

RoHS compliant*4

Shock Resistance

 $9.806 \, \text{km/s}^2 \, \{1,000 \, \text{G}\} \, 0.5 \, \text{ms} \, \text{half sine wave}$

Vibration

196 m/s² {20 G} Peak, 10~2,000 Hz, (20 min / Axis) x 3 Axis

Supply Voltage

3.3V ± 5%

Power Consumption (Active)

500GB, 1TB: 3.5 W (typ.) 2TB: 5.3 W (typ.) **Power Consumption**

PS3: 50 mW (typ.) PS4: 5 mW (typ.)

Compatibility

PCI Express

Compatible with PCI Express® Base Specification Revision 3.1a and NVM Express™ Revision 1.3c command set

Connector Type M.2 M key Socket

Target Applications

Client desktops and laptops

Additional Features

Services and Support

Up to 5-year manufacturer's warranty

MANUFACTURER'S WARRANTY IS EFFECTIVE EITHER (I) WARRANTY PERIOD FROM THE DATE OF PURCHASE IN ITS ORIGINAL SEALED PACKAGING OR (II) FOR THE TIME PERIOD UNTIL THE "PERCENTAGE LIFE LEFT" WILL BE ZERO, WHICHEVER IS SHORTER. The "Percentage Life Left" can be found using "Health" gauge of the SSD Utility for KIOXIA products, which is available at "personal.kioxia.com/support/".

Performance Optimization

TRIM, Idle Time Garbage Collection

SSD Management Software

Please visit our website for information on the required OS version at "personal.kioxia.com".

Ordering Information

Global Package:

500GB 1TB 2TB

PN: LRC20Z500GG8 PN: LRC20Z001TG8 PN: LRC20Z002TG8
EAN: 4582563853980 EAN: 4582563853997 EAN: 4582563854000

China Package:

500GB 1TB 2TB

PN: LRC20Z500GC8 PN: LRC20Z001TC8 PN: LRC20Z002TC8 EAN: 4582563854017 EAN: 4582563854024 EAN: 4582563854031

¹ EXCERIA G2 SSD: Sequential speeds are measured with CrystalDiskMark 8.0.1 x64, Q=32, T=1. These values are the best values obtained in a specific test environment at KIOXIA Corporation and KIOXIA Corporation warrant neither read nor write speeds in individual devices. Read and write speed may vary depending on a device used and file size read or written.

² EXCERIA G2 SSD: 4KiB random performance is measured with CrystalDiskMark 8.0.1 x64, Q=32,T=16. These values are the best values obtained in a specific test environment at KIOXIA Corporation and KIOXIA Corporation warrant neither read nor write speeds in individual devices. Read and write speed may vary depending on a device used and file size read or written.

³EXCERIA G2 SSD: Definition and conditions of TBW (Terabytes Written) are based on JEDEC standard; JESD219A Solid-State Drive (SSD) Endurance Workloads, July 2012, and defined for the service life.

*KIOXIA Corporation defines "RoHS Compatible" products as products that either (i) contain no more than a maximum concentration value of 0.1% by weight in Homogeneous Materials for lead, mercury, hexavalent chromium, polybrominated biphenyls (PBBs), polybrominated diphenyl ethers (PBDEs), bis[2-ethylhexyl) phthalate (DEH), dibutyl phthalate (DBP), benzyl buyl phthalate (DBP) and disobutyl phthalate (DBP) and of 0.01% by weight in Homogeneous Materials for cadmium; or (i) | Xell within any of the application exemptions set forth in Annex to the P6HS Directive"). This does not mean that Kloxia Corporation products labeled "RoHS COMPATIBLE" are entirely free of substances controlled by the RoHS Directive and does not constitute a warranty or guarantee that such products will comply with the specific laws and/or regulations adopted in any particular jurisdiction.

RoHS Directive: KIOXIA Corporation defines "RoHS Directive" as the DIRECTIVE 2011/65/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

Definition of capacity, KIOXIA defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2^m = 1,073,741,824 bytes and therefore shows less storage capacity, Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may be a capacity and the content of the content of

Read and write speed may vary depending on the host device, read and write conditions, and file size

Product specifications and design are subject to change without prior notice.

Product images may represent design model. Actual product may vary.

A kibibyte (KiB) means 210, or 1,024 bytes, a mebibyte (MiB) means 220, or 1,048,576 bytes, and a gibibyte (GiB) means 220, or 1,073,741,824 bytes

IOPS: Input Output Per Second (or the number of I/O operations per second)

MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

To protect against accidental data loss, back up your data frequently on other storage media. KIOXIA Corporation does not warrant any data stored on the product

For safety instructions, please visit: personal.kioxia.com/support/

NVM Express and NVMe are registered or unregistered mark of NVM Express, Inc. in the United States and other countries

PCIe, PCI Express and PCI-SIG are registered trademarks of PCI-SIG.

Other company names, product names, and service names may be trademarks of third-party companies.

The line up of personal product vary by country and region.